



bizhub® C3851FS

COLOR COMPACT MULTIFUNCTION PRINTER

Fast print/copy output of 40 ppm in color and B&W	
Standard Super G3 fax	
Standard stapler inner-finisher	
Downloadable apps to help you work faster and smarter	
Advanced scan capture functionality right from the touchscreen control pa	anel
Built-in Emperon® print system, PCL and PostScript emulation	



Large 7" touchscreen with logical, intuitive menus — as easy to operate as	a familiar tablet
Open API for seamless software integration	
Compatibility with IC card readers for enhanced security	
Standard wireless connectivity	
Mobile printing support (AirPrint, Google Classic Cloud Print™, NFC)	

bizhub C3851FS

COLOR COMPACT MULTIFUNCTION PRINTER

The bizhub** C3851FS provides brilliant color quality and fast 40 ppm output to help you keep ahead of rising document demands. The advanced Emperon print system, standard wireless connectivity and web browser, standard stapler inner-finisher, high-speed fax and intuitive touchscreen operation make this a valuable stand-alone solution or versatile addition to mixed networks of large and small MFPs.

SYSTEM OVERVIEW

System memory	4 GB (when UK-211 is installed)	
System hard disk	250 GB (standard)	
Interface	10-Base-T / 100-Base-TX / 1,000-Base-T Ethernet, USB 2.0	
Network protocols	TCP/IP (IPv4 / IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS	
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP	
Reversing automatic	Up to 50 originals / 5.5" x 8.5" to 8.5" x 14" / 50-128 gsm	
document feeder		
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes	
Printable paper weight	60-210 gsm	
Paper input capacity	Standard: 650 sheets / Max.: 1,650 sheets	
Tray 1	550 sheets / 4" x 6" to 8.5" x 14" / 60-210 gsm	
Tray 2-3 (optional)	500 sheets / 8.5" x 11 to 8.5 x 14" / 60-90 gsm	
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14" / custom paper sizes /	
	60-210 gsm	
Automatic duplexing	Letter, legal / 60-210 gsm	
Finishing modes	Staple (inline) up to 50 sheets	
Output capacity	Max.: 250 sheets	
Copy/print volume	Max.: 120,000 pages / month ¹	
Toner lifetime	K: 13K CMY: 12K	
Imaging unit lifetime	K: 70K CMY: 60K	
Power consumption	120 V / 60 Hz, less than 1.7 kW (system)	

PRINTER SPECIFICATIONS

Print resolution	600 x 600 dpi, 1,200 x 1,200 dpi (reduced speed)		
PDL	PCL5e/c emulation, PCL XL ver. 3.0, PostScript 3 emulation		
	(3016), XPS ver. 1.0, OpenXPS, PDF 1.7		
Operating systems	Windows (x64): XP / Vista / 7 / 8		
	Windows Server (x64): 2008 / 2008 R2 / 2012		
	Macintosh OS X 10.6 or later		
	Linux / Citrix		
Printer fonts	80 PCL Latin, 137 PostScript 3 Latin		
Print functions	Direct print of TIFF, XPS, PDF and OOXML (DOCX, XLSX,		
	PPTX), secure print, combination, n-up, poster, booklet		
	page order, watermark		

FAX SPECIFICATIONS

Fax	Super G3 (standard)	
Transmission	Analog, PC-fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Time shift, PC-fax, fax forwarding, up to 400 program dials	

OPTIONS

nologies	
r	
lia, etc.	
1/1b)	
Supports native barcode printing	

bizhub_C3851FS_Spec_Sheet

System dimensions	21.9" x 22.9" x 23.7" (W x D x H)		
System weight	Approx. 116 lb		
COPIER SPECIFICATIONS			
Copying process	Electrostatic laser copy, tandem, indirect		
Toner system	Simitri® HD Polymerized Toner		
Print speed	Up to 40 ppm (letter, mono/color)		
Autoduplex speed	Up to 40 ppm (letter, mono/color)		
1st copy out time	9 sec./10 sec. (mono/color)		
Warm-up time	Approx. 30 sec. ²		
Copy resolution	600 x 600 dpi		
Gradations	256 gradations		
Multi-copy	1–999		
Original format	Max.: up to 8.5" x 14"		
Magnification	25-400% in 1% steps, auto zooming		
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1		

21 0 ... 22 0 ... 22 7 ... (W., D., 11)

Security		

PF-P13 Paper tray **UK-211 Expanded memory**

WT-P02 Working table

LK-108

LK-111

MK-P02

LK-110 v2

SYSTEM FEATURES ISO 15408 EAL3 (in evaluation), IP filtering and port blocking, SSL2, SSL3 and TSL1.0 network communication, IPsec support, IEEE 802.1x support, user authentication, secure print, HDD overwrite (8 standard types), HDD data encryption, copy protection (print only) Software PageScope Net Care Device Manager, PageScope Data Administrator, PageScope Direct Print, PageScope Mobile, Print Status Notifier, Driver Packaging Utility

Supports native OCR A and B font printing

and combines LK-102 + LK-105

Installation kit for IC card reader

Authentication device placement

2 GB memory extension3

Generates various file formats including DOCX, XLSX

8.5" x 11" to 8.5" x 14" / 500 sheets / up to 90 gsm

ThinPrint®, print data compression for reduced network impact

³ Required for full functionality



Up to 37 opm (mono/color)



SCANNER SPECIFICATIONS

Scan speed



For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

 $\textcircled{\textbf{@ 2017 KONICA MIN OLTA BUSINESS SOLUTIONS U.S.A., INC.}} \ All \ rights \ reserved. \ Reproduction \ in \ whole \ or \ in \ part \ without \ written \ permission$ is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions describedhere may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com







9/2017-C

Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

²Warm-up time may vary depending on the operating environment and usage